

January 14th, 2020 – Andrew Poerschke, IBACOS

Ductwork in Attics, One of the Last Holdouts of Inefficient Home Design

www.phrc.psu.edu


PennState College of Engineering PENNSYLVANIA HOUSING RESEARCH CENTER

NARI CEU Approved IBC PREFERRED EDUCATION PROVIDER PHRC



Overview

- HVAC Design Process
- Review Code Changes
- Discuss Duct Strategies and Risks
- Examples
- Conclusions





Mechanical design process (dysfunction)


- Architect designs house
- House is engineered and optimized for framing cost
- HVAC designer is given house and framing plan and tasked with fitting ductwork in the least invasive way possible
- HVAC designer knows keeping ductwork compact and within insulation envelope is best, but keeps running into problems
 - Chase is too big
 - Staircase in the way
 - Structural beam in the way
- Ducts are large and a challenge to integrate

Result:

- HVAC designer ends up putting ductwork outside of the house, in the attic, crawlspace, garage or basement.
- Excessively long runs are needed to go around obstructions, requires bigger ducts
- Convoluted plans that are difficult to follow
- Comfort is compromised
- Increased energy use

The problem with ductwork outside of the envelope

- 10-40% increase in load
 - Larger / more expensive equipment
 - Bigger ductwork and fittings
- Increased Energy Consumption
- Condensation and durability risks
- Comfort risks
 - Milder delivery temperature
 - Slug of cold / hot air





Heating Summary	
Structure	30018 Btu/h
Ducts	3256 Btu/h
Central vent (60 cfm)	4428 Btu/h
Outside air	0 Btu/h
Humidification	0 Btu/h
Piping	0 Btu/h
Equipment load	37703 Btu/h

Heating Summary		Sensible Cooling Equipment Load Sizing	
Structure	23454 Btu/h	Structure	20775 Btu/h
Ducts	7558 Btu/h	Ducts	8953 Btu/h
Central vent (121 cfm)	4598 Btu/h	Central vent (121 cfm)	3333 Btu/h
Outside air	0 Btu/h	Outside air	0 Btu/h
Humidification	0 Btu/h	Blower	0 Btu/h
Piping	0 Btu/h	Use manufacturer's data	0 Btu/h
Equipment load	34110 Btu/h	Manufacturer's data	0 Btu/h

Something needs to change

ACCA Manual J

- Calculate building total thermal load and zone requirements
- Should be specific to orientation
 - Plans with inadequate exposure diversity may see ½ ton + change in load
 - Master bedroom design changes from 75 – 90 CFM (20%)
- Should be specific to exact options package.
 - Ex: Sliding glass door adds 100 CFM
- Internal gains should reflect design and intended occupancy




ACCA Manual S

- Equipment selection
 - Multi-step process accounts for various environmental factors
 - Outdoor drybulb
 - Indoor wetbulb
 - Airflow
 - Reference manufacturer data
 - Furnace capacity should be no more than 40% greater than load
 - Air conditioner capacity should be no more than 15% greater than load
- Fan speed selection
 - Fan speed should be specified for correct SHR
 - Fan speed must be set by mechanical contractor



ACCA Manual D / T

- Sizing supply and return duct runs
 - Fundamentally oversized, not predictive or balanced
- Sized for max of cooling and heating load
 - Different for cooling / heating dominate climates
 - Systems don't automatically adjust seasonally
- Designing return air pathways
 - Maintain < 3Pa between rooms and hallways
 - Specify large enough or thick enough filters, furnace side may not be big enough
- Specify register sizes
 - Should be selected for velocity, throw and noise
 - Usually few sizes selected to save \$



What's missing?

- Framing plan integration
- Who should own the design?
 - HVAC contractor?
 - Builder?
 - Central design firm?
- Feedback loop with Architect





Code Changes

- Prior to 2018 IECC the code did not specifically address buried ductwork
 - Inconsistent treatment in different jurisdictions
 - No specific requirements for condensation control
 - No credit for energy savings
- Code adopting buried duct language as a concession to the challenges of bringing conventional ductwork into conditioned space.
- PA has Section R403.3.6 & R403.3.7 of 2018 IECC

R403.3.6:

- "Where supply and return air ducts are partially or completely buried in ceiling insulation, such ducts shall comply with all of the following:"
 - Supply and return R-8 min
 - R-19 minimum sum of ceiling insulation around duct
 - R-13 minimum duct insulation CZ1A,2A,3A
 - EXCEPTION: Sections of the supply duct that are less than 3 feet from the supply outlet shall not be required to comply with these requirements
- Given min 3.5" insulation above, and max 5.5" below, effective R-value of R-25 can be claimed

2018 - IECC, International Code Council

R403.3.7 :

- "For ducts to be considered inside a conditioned space..."
- "The duct system shall be located completely with the continuous air barrier and within the building thermal envelop."
- Ducts shall be buried according to R403.3.6 and:
 - AHU must be with the "continuous air barrier"
 - Duct leakage less than 1.5 CFM₂₅ per 100 ft²
 - Ceiling insulation = R ceiling – R duct (R-49 – R-8 = R-41)


2018 - IECC, International Code Council

Duct Strategies

Strategy	Performance	Cost	Risk	Ease
Attic exposed	*	\$	*	***
Attic unvented	**	\$\$\$	*	***
Attic partly buried	***	\$	**	**
Attic deeply buried	***	\$	***	*
Conditioned space	***	\$	*	*
Ductless	***	\$	*	**



Buried Ducts



Examples

HIRL Study - Compact ducts buried

- Buried duct strategy with no encapsulation
- Hot / humid climate
- Found no condensation on R-8 ducts in Maryland / New Jersey / South Carolina
- Complex phenomena of moisture transport through attic insulation
- Worked well under controlled environment



Compact Buried Ducts in a Hot-Humid Climate House - HIRL 2016

Images from HIRL

CARB Study - Buried and encapsulated

- Several studies have shown this is an effective option for reducing risk of condensation
- Effective with 1.5" ccSPF over R-4.2 and 1.0" ccSPF over R-6
- May require adjusting construction schedules and multiple trips for the insulation contractor.



Images from CARB
"Reducing Thermal Losses and Gains With Buried and Encapsulated Ducts in Hot-Dry Climate" CARB - 2013


Benefits

- Can claim higher R value for ductwork
 - R-25
 - Ducts in conditioned space
- Shorter, more compact runs
 - Savings on duct material
 - More efficient delivery of air
- Straighter runs when not hung
 - Lower static pressure
- Possible duct installation speed improvements



Risks

- Complexity of code
 - Many acceptable scenarios
 - Difficulty in inspection
- Condensation
 - Must make sure ducts are not touching
- Installation Complexity
 - Must be done perfectly, relying on materials to perform
- Quality Control
 - Difficult to verify insulation amount and quality underneath plenums and ducts.
 - Once buried, cannot confirm correct installation.




How much condensation is a problem


- Brief occurrences of condensation are likely to dry
- More research needed to fully characterize the phenomena
- Risk goes up significantly if ducts are crossing / touching
- Lower temperature at register / boot, increased condensation potential



R-8 Hung



R-13 duct under R-25



Conditioned Space

Conditioned Space

- Benefits
 - Less risk
 - Lower tonnage equipment
 - ERI Improvement
 - Different leakage testing requirements
- Challenges
 - Structural integration
 - Aesthetic impact
 - Large duct sizes
 - Routing returns
 - Rooms over garages



Conditioned Space

- Can work well but requires:
- Planning
- Putting structural changes on the table
 - Taller ceiling height (>8 ft) on first floor
 - Joist orientation
 - Joists bear on walls, not beams
 - Interior wall location and thickness
 - Central chases
 - Stair location
 - Open web trusses
 - Drop ceilings and soffits
- Mechanical closet




Conditioned Space Example



Multi-family

- Frequently ductwork already in conditioned space
- Limited space and access constraints
- Enabled by use of better planning and open web trusses.



Multi-family example

- Dropped ceiling over portion of living space
- Ceiling and floor registers
- Equipment in conditioned space
- Vertical chase to second floor



Alternatives



Ducted MSHP



Smaller Ducts



Concluding Thoughts

- Codes are moving toward more efficient requirements for ductwork
- Buried ductwork may be a temporary strategy to ease transition, research shows it can work, but still ongoing. Condensation and moisture is a complex phenomena.
- Buried ductwork must be done with care and rigor not always seen in the industry.



Concluding Thoughts

- Not a challenge technology alone can solve
- Ultimate goal is ductwork actually within conditioned space, but this will require true mechanical integration
- Collaboration is key



Resources / References

- Buried Duct Tech Spec
<https://www.homeinnovation.com/~media/Files/Reports/TechSpec-Buried-Ducts-2017.pdf>
- Compact Buried Ducts in a Hot-Humid Climate House:
https://www1.eere.energy.gov/buildings/publications/pdfs/building_america/compact-buried-ducts-hot-humid.pdf
- Reducing Thermal Losses and Gains With Buried and Encapsulated Ducts in Hot-Humid Climates:
https://www1.eere.energy.gov/buildings/publications/pdfs/building_america/encaps_ducts_hothumid.pdf
- Buried Ducts: Advantages, Challenges, and New Options in the 2018 IECC :
https://www.energycodes.gov/sites/default/files/becu/Buried_Ducts_Webinar_Presentation_Slides.pdf



Ductwork in Attics, One of the Last Holdouts of Inefficient Home Design

www.phrc.psu.edu





